

Technical Information – MBF 25(C) USB/RJ45

Cable gland with slotted sealing insert, polyamide light grey, IP 66/68

Model	Order no.	Note
MBF 20-RJ45	12002418	Max. connector ø 14.5 mm, cable ø 3-6 mm
MBF 25C-USB	12002414	Max. connector ø 17.0 mm, cable ø 3-8 mm
MBF 25-USB	12002404	Max. connector ø 18.5 mm, cable ø 3-8 mm

Notes: With slitted sealing insert for mounting cables with a connector.



Material

- Nut / Neck
- Sealing insert

Temperature range

Protection acc. IEC 60529

Protection acc. UL50E

Test standard

DNV Certified

- Polyamid 6 V-2
- Chloropren CR H
- -20°C / +100°C (dynamisch)
- IP 66, IP 68, IP 69K
- 4X, 12, 13
- UL 514B
- UL 50E
- Ships
- Offshore installations
- High-speed and light vehicles

Tested and certified according to:

- UL514B
- UL50E
- CAN/CSA C22.2 No. 18.3-12
- CAN/CSA C22.2 No. 94.2-15

Meets the requirements of DNV GL rules for the classification of ships, offshore installations, high-speed and light vehicles.

BOPLA
A Phoenix Mecano Company

Please note!

Technical information is provided to the best of its knowledge, but does not exempt the user from checking the suitability of this information for the intended processes and purposes.