

Technical Information - MEMV



Metric EMC cable glands MEMV, brass, nickel-plated, IP 68 (5 bar, 30 min)

Model	Order no.	Note
MEMV 16	12102200*	M16 x 1.5; cable diameter 5-9 mm
MEMV 20	12102300*	M20 x 1.5; cable diameter 9-13 mm
MEMV 25	12102400*	M25 x 1.5; cable diameter 11-16 mm
MEMV 32	12102500*	M32 x 1.5; cable diameter 14-21 mm
MEMV 40	12102600	M40 x 1.5; cable diameter 19-27 mm

Material

- Nut / Neck
- Seal
- Slat insert
- O-ring
- Contact spring
- Brass CuZn39Pb3, galv. nickel-plated
- Polychloroprene nitrile rubber CR/NBR
- Polyamide PA6 V-2
- Nitrile Rubber NBR
- Stainless steel

Temperature range

- -20°C / +100°C (dynamic)
- -40°C (static, short-term)

Protection

- IP 68
- 5 bar (30 min)

Test standard

- UL 514B

Tested and certified according to:

- UL514B
- CAN/CSA C22.2 No. 18.3-04



BOPLA

A Phoenix Mecano Company

Please note!

Technical information is provided to the best of its knowledge, but does not exempt the user from checking the suitability of this information for the intended processes and purposes.